



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : A61B 5/00	A1	(11) International Publication Number: WO 00/13576 (43) International Publication Date: 16 March 2000 (16.03.00)
(21) International Application Number: PCT/US99/20234 (22) International Filing Date: 3 September 1999 (03.09.99) (30) Priority Data: 60/099,579 9 September 1998 (09.09.98) US 60/101,143 18 September 1998 (18.09.98) US (71) Applicant (for all designated States except US): U.S. ARMY INSTITUTE OF SURGICAL RESEARCH [US/US]; Building 3611, 3400 Rawley E. Chambers, Fort Sam Houston, TX 78234-6315 (US). (72) Inventors; and (75) Inventors/Applicants (for US only): WALKER, Steven, C. [US/US]; 467 East Olmos Drive, Olmos Park, TX 78212 (US). SHEPHERD, John, M. [US/US]; 461 Graham Street, Fort Sam Houston, TX 78234 (US). ALEXANDER, John, G. [US/US]; 169 Liberty Crossing, O'Fallon, IL 62269 (US). (74) Agent: HARRIS, Charles, H.; Cahn & Samuels, LLP, Suite 200, 2000 P Street N.W., Washington, DC 20036 (US).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: NASOPHARYNGEAL AIRWAY WITH REFLECTANCE PULSE OXIMETER SENSOR <div data-bbox="329 1163 1269 1430" data-label="Image"> </div> (57) Abstract <p>A combined nasopharyngeal airway and pulse oximeter sensor capable of monitoring the posterior pharynx, posterior soft palate or nasal mucosa is disclosed. The nasopharyngeal airway (10) includes a thickened wall section (12) over approximately one-third of its circumference. Pulse oximeter sensor elements (20, 22, 24, 26) may be embedded in the airway. The pulse oximeter sensor elements may include a light source (20), which preferably emits light at wavelengths around 660 nm (red) and around 940 nm (near infrared), and a light detector (22). The pulse oximeter sensor elements may be connected to a pulse oximeter monitor (spectrophotometer) or other external device for analysis.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

NASOPHARYNGEAL AIRWAY WITH REFLECTANCE PULSE OXIMETER SENSOR

I. TECHNICAL FIELD

5 The invention relates to the field of reflectance oximetry. More particularly, the invention is directed to a nasopharyngeal airway with a reflectance pulse oximeter sensor.

II. BACKGROUND ART

 With a few exceptions, tradition and technology have favored
10 transillumination pulse oximetry in the operating theater. The principle of operation of the pulse oximeter is fairly simple but is arguably the most important development in anesthesia monitoring in the twentieth century. Two wavelengths of light (usually 660 nm and 940 nm) are used to spectrophotometrically determine the ratio of oxidized to reduced hemoglobin
15 noninvasively as well as to determine the pulsatility of blood plethysmographically. Presently, the most common application of this in the operating theater is via transillumination through the capillary bed of a peripheral digit. However, it is not unusual for multitrauma and thermally injured patients to either have severe peripheral vasoconstriction or to have severely damaged (or
20 missing due to amputation) peripheral vascular beds. Reflectance oximetry rather than transillumination oximetry was the earliest investigative form of the technique. Transillumination pulse oximetry, without question, is the most effective form when oximetry is obtained through skin. However, when skin is not interposed as a barrier to capillary bed access, reflectance pulse oximetry
25 easily can be achieved with very accurate results. The effect is achieved by the backscattering of incident bispectral light that traverses and, on reflection from nonabsorptive collagenous tissues, retraverses formed elements in the blood back to the oximetric detector. Rather than superseding transillumination pulse oximetry, this technique broadens the scope of possible monitoring sites, adding
30 to the clinician's armamentarium.

Conventional pulse oximetry in the severely burned patient can be a significant challenge, yet this monitoring data is vital in operating room and intensive care settings. Most current oximetric approaches depend upon available peripheral sites permitting transillumination oximetry and indeed, this method is sufficient for most surgical conditions and procedures. Unfortunately, patients with severe burns often have few sites for the effective placement of the transilluminating pulse oximeter sensor. In addition, these patients often have severe circulatory compromise rendering the peripheral pulse oximeter less efficient. A variety of studies have shown that central pulse oximeters are more reliably and rapidly responsive than peripheral pulse oximeters.

Reflectance oximetry can be a useful tool where a capillary bed is easily accessible. Indeed, it is used commonly and effectively among intrapartum and neonatal patients whose capillary beds are easily accessed through their skin. The technique has also been applied to adult and pediatric burn patients by placing the reflectance sensor in wounds or over hyperemic sites such as healed partial thickness burns.

The nasal mucosa and the posterior pharynx contain rich capillary beds ideal for reflectance pulse oximetry. Known pulse oximeters are not suitable for use in the nares as they tend to block the nasal passage thus constricting the patient's breathing. In addition, they are prone to difficulties when their electrical components are exposed to liquid, moisture, bodily fluids, and/or surgical fluids. Since they rely on transillumination they also tend to be difficult to hold in place. Accordingly, a need exists for a more convenient device that combines a pulse oximeter sensor with a nasopharyngeal airway.

Nasopharyngeal airways are used in the operating room to establish communication between the nares and the posterior pharynx. Nasopharyngeal airways also are used to perform nasal suctioning.

III. DISCLOSURE OF THE INVENTION

The invention while addressing the problems of the prior art obtains advantages that were not achievable with the prior art devices.

An object of this invention is to provide an effective device for taking pulse oximetry measurements from nasal and posterior pharyngeal capillary beds.

Another object of the invention is to eliminate the need for employing a separate nasopharyngeal airway when taking pulse oximetry measurements via
5 the nasal cavity.

Another object of the invention is the use of reflectance pulse oximetry via the nasal cavity for a variety of surgical, anesthetic, or critical care procedures performed on patients who are awake, sedated or undergoing general anesthesia.

10 Another object of the invention is to provide a pulse oximeter in a sealed body that is fluid impermeable.

An advantage of the invention is an improvement in the quality of care resulting from not needing to switch devices or use two separate devices in the nasal cavity.

15 Another advantage of the invention is improved pulse oximetry readings regardless of the radial position of the device when it is placed in the nares.

Given the following enabling description of the drawings, the apparatus should become evident to a person of ordinary skill in the art.

IV. BRIEF DESCRIPTION OF THE DRAWINGS

20 Figure 1 illustrates a side view of a preferred embodiment.

Figure 2 illustrates a radial cross-section view of the embodiment shown in Figure 1.

Figure 3 illustrates a rear view of the embodiment shown in Figure 1.

Figure 4 illustrates a bottom view of the embodiment shown in Figure 1.

25 Figure 5 illustrates the embodiment shown in Figure 1 in use in a patient.

V. BEST MODES FOR CARRYING OUT THE DESCRIBED EMBODIMENTS

Figures 1-5 illustrate a preferred embodiment of the pulse oximeter sensor assembly according to the invention. The pulse oximeter sensor assembly includes a nasopharyngeal airway 10 in combination with pulse oximeter elements 20, 22, 24, and 26. The pulse oximeter sensor elements 20, 22, and 24 are preferably disposed within the wall of the nasopharyngeal airway. Preferably, the wall of the nasopharyngeal airway is made of a clear polymer. Furthermore, it is preferable that the wall may include a thickened section 12 around approximately one-third of the circumferential area to house the pulse oximeter sensor elements 20, 22, and 24. Alternatively, the thickened section 112 may be around just the elements themselves and not run the length of the wall.

As depicted in Figure 1, the nasopharyngeal airway 10 is preferably a hollow, elongated member defining a passageway, e.g., a cylindrical tubular member, having an insertion end 14 and a base end 16. The insertion end 14 is preferably angled. The base end 16 may be flat and disposed substantially perpendicular to the rest of the nasopharyngeal airway or angled. The base end 16 may include a notch or other marking corresponding to the tip of the nasopharyngeal airway 10 to assist the user in further positioning the device in the patient after insertion of the device.

The pulse oximeter sensor elements 20, 22, and 24 are preferably disposed in the thickened wall section 12 of the nasopharyngeal airway 10. Alternatively, the pulse oximeter sensor elements 20, 22, and 24 may be disposed within the passageway of nasopharyngeal airway 10. The pulse oximeter sensor elements include a light source 20, which preferably emits light with wavelengths of 660 nm (red) and 940 nm (near infrared), a light detector 22 and wiring 24. These pulse oximeter sensor elements are preferably embedded and sealed in the wall of the nasopharyngeal airway with a cover protecting them. Preferably, the cover is a clear, fluid impermeable plastic.

The light source 20 may include more than one emitter. The light source may be one or more of the following: a pair of light emitters such as light emitting

diodes (LEDs), a single light emitter, a bispectral emitter, a dual spectral emitter, a photoemitter, a photodiode, or a semiconductor die. However, any light source that facilitates reflectance pulse oximetry may be employed. When the light source 20 is one light emitter then the light emitter, for example, preferably would
5 emit two frequencies of light at about 660 nm and about 940 nm. Typically, the two emitter arrangement will include a red LED near 660 nm and a near-infrared LED emitting in the range of 890nm to 950 nm. The light source 20 may emit light having a bandwidth in the range of 20 to 50 nm.

A light detector 22 detects light emitted by light source 20. Electrical
10 signals representing the detected light are transmitted by light detector 22 to a spectrophotometer or pulse oximeter that discriminates between the relative intensity of these emissions and provides an index as to the degree of oxygen saturation of hemoglobin in blood. The light detector 22 may be one of the following: a photoelectric receiver, a photodetector, a photodiode receiver, or a
15 semiconductor die.

The wiring 24 connects the pulse oximeter sensor elements to an external cord 26 that may also be embedded in the thickened wall section 12 of the nasopharyngeal airway 10. The wiring 24 includes conductive lines and contact electrodes. The light source 20 and the light detector 22 are each connected to
20 their own contact electrode, respectively. The external cord 26 preferably is insulated and connects to the nasopharyngeal airway 10 at the base 16. The external cord 26 has a standard and universal plug design to interface with a pulse monitor, such as a plethysmograph or a pulse oximeter, or other external device. Although not shown, light source 20 and light detector 22 may comprise
25 a wireless pulse oximeter sensor. Preferably, the pulse oximeter sensor elements are used for reflective oximetry as opposed to transillumination oximetry.

In accordance with a preferred aspect of the invention, the pulse oximeter sensor elements 20 and 22 may be located near the angled end 14 to facilitate
30 readings taken from the proximal posterior pharynx as shown in Figure 5. This arrangement provides for easy access and a reliable contact point. However, if the pulse oximeter sensor elements 20 and 22 are located near the base end 16,

then the readings will be taken from within the nasal cavity. The nasal cavity provides less reliable and accurate pulse oximetry readings than the posterior pharynx.

In use, the nasopharyngeal airway 10 preferably takes measurements from a central measurement site, namely the proximal posterior pharynx, posterior soft palate or nasal mucosa. The data collected from these locations has proven more reliable than data attainable from periphery locations. The increased reliability is believed to be due to the centrality of the measurement location and the stability of the measurement surfaces. The measurement indicates the oxygen saturation of hemoglobin. Furthermore, the nasopharyngeal airway of this invention is extremely useful in cases where it is difficult at best or not even possible to attach prior art pulse oximeter sensors with clips or straps to the patient. The nasopharyngeal airway of this invention is useful with patients who are critically ill or injured patients including burn or trauma patients without alternative sites and maxillofacial injuries.

The invention is particularly useful when the patient is awake but sedated. However, the invention may be used while the patient is fully awake, during induction of anesthesia, during general anesthesia, on emergence from anesthesia and during recovery. The invention is particularly useful in very wet environments as the oximetric components and wiring are sealed within the polymeric envelope of the nasopharyngeal airway. The invention is useful in field and emergency medical areas in that it can both establish an airway and provide pulse oximetry monitoring in a single device.

The nasopharyngeal airway will preferably be manufactured using polypropylene, polyvinyl chloride, silicones, epoxies, polyester, thermoplastics, rubber, similar flexible material, etc. The material should be sufficiently flexible that it freely bends in accordance with the contour of the nasal passageway. The thickened area is preferably formed from a clear or semi-translucent material to allow for the passage of light from the light source 20 and to the light detector 22.

In keeping with the invention, the pulse oximeter elements may be attached to or disposed adjacent to an internal surface of the passageway. A disposable pulse oximeter like the Nellcor® Oxisensor® II N-25 or D-25 (Nellcor

Puritan Bennett®, Inc., Pleasanton, California) may be stripped of its surroundings to leave only the pulse oximeter elements. The pulse oximeter elements may then be feed into the nasopharyngeal airway 10 along one side of the passageway. Even though the pulse oximeter elements and wiring may be present in the passageway, there is sufficient airflow capacity to supply adequate oxygen to the patient.

The method of taking pulse oximeter readings from posterior pharyngeal area within a patient has been submitted to actual testing in the below-described population and according to the following protocol.

10 The protocol involved comparing posterior pharyngeal reflectance pulse oximetry to conventional peripheral transillumination pulse oximetry in difficult to monitor burn patients. Eight patients' records were reviewed over fourteen consecutive surgical procedures, all consisting of excision and grafting. Patients ranged in age from 9 to 43 years and ranged from 14.5% to 77.5% total body surface area (%TBSA) burned (Mean = 30.4, SD [standard deviation] = 22.1).
15 The number of operations per patient ranged from one to four.

A Nellcor® Oxisensor® II pulse oximeter probe was placed in the distal lumen of an appropriately sized oropharyngeal airway with sensor and emitter facing the posterior pharynx. A similar probe was placed on a peripheral digit as
20 a transilluminating pulse oximeter. SpO₂ values were noted at five-minute intervals. Concordance statistics as well as a *t*-test for correlated means were calculated between the simultaneously obtained SpO₂ values.

The mean differences between pharyngeal reflectance and peripheral digital transillumination SpO₂ values were insignificant for all cases.
25 Concordance statistics were as follows: 0.75 (*n* = 1) and 1.0 (*n* = 12).

Given the near perfect concordance statistics in this study, this data suggests that posterior pharyngeal reflectance oximetry is a simple, highly accurate means of monitoring arterial oxygen saturation in the severely burned patient where oximetric monitoring presents a challenge.

VI. INDUSTRIAL APPLICABILITY

The invention is particularly useful for monitoring the blood oxygen content of a subject. The invention may be used by hospital personnel, emergency medical crews, in-home medical personnel, laboratory and veterinary personnel
5 and battle field medical personnel.

Those skilled in the art will appreciate that various adaptations and modifications of the above-described preferred embodiments can be configured without departing from the scope and spirit of the invention. Therefore, it is to be understood that, within the scope of the appended claims, the invention may be
10 practiced and constructed other than as specifically described herein.

IN THE CLAIMS:

We claim

1. An oximetry measurement device comprising:
a base having a hole passing therethrough,
an elongated member extending from said base, said elongated member
having a passageway passing therethrough, the passageway being in
5 communication with the hole of said base, and
pulse oximeter sensor elements embedded in said elongated member.
2. The device according to claim 1, wherein said elongated member is
a cylindrical tube having a wall of non-uniform thickness.
3. The device according to claim 2, wherein the wall includes a first
section and a second section, the second section being thicker than the first
section and the pulse oximeter sensor elements being embedded in the second
section.
4. The device according to claim 1, wherein said pulse oximeter
sensor elements include:
a light source, and
a light detector in communication with the light source.
5. The device according to claim 4, wherein said light source includes
one of at least one light emitter, a bispectral emitter, a dual spectral emitter, at
least one photoemitter, at least one photodiode, at least one light emitting diode,
and a semiconductor die.
6. The device according to claim 4, wherein said at least one light
detector includes one of a photoelectric receiver, a photodetector, a photodiode
receiver, and a semiconductor die.
7. The device according to claim 1, wherein said pulse oximeter
sensor elements include:
means for transmitting light, and
means for receiving light transmitted by said means for transmitting light.

8. A method for taking oximetry readings from a posterior pharyngeal region of a patient, said method comprising:
- coupling the device recited in claim 1 to a pulse oximeter,
 - inserting the elongated member of the device recited in claim 1 through a
 - 5 nasal cavity of the patient,
 - aligning the pulse oximeter sensor elements of the device according to claim 1 with the posterior pharyngeal region of the patient, and
 - contacting the pulse oximeter sensor elements of the device according to claim 1 with the posterior pharyngeal region of the patient.
9. A device according to claim 1, wherein said elongated member is made from flexible material including a portion capable of transmitting light.
10. A method for taking oximetry readings from a nasal mucosa of a patient, said method comprising:
- coupling the device recited in claim 1 to a pulse oximeter,
 - inserting the elongated member of the device recited in claim 1 through a
 - 5 nasal cavity of the patient,
 - aligning the pulse oximeter sensor elements of the device according to claim 1 with the nasal mucosa of the patient, and
 - contacting the pulse oximeter sensor elements of the device according to claim 1 with the nasal mucosa of the patient.
11. A device comprising:
- a base having a hole passing therethrough,
 - an elongated member extending from said base, said part having a
 - 5 passageway passing therethrough, wherein the passageway being in communication with the hole of said base, and
 - pulse oximeter sensor elements disposed in the passageway.
12. The device according to claim 11, wherein said elongated member is a cylindrical tube.

13. The device according to claim 11, wherein the wall includes a first section and a second section, the second section being thicker than the first section and the pulse oximeter sensor elements being embedded in the second section.

14. The device according to claim 11, wherein said pulse oximeter sensor elements include:

- a light source, and
- a light detector in communication with the light source.

15. The device according to claim 14, wherein said light source includes one of at least one light emitter, a bispectral emitter, a dual spectral emitter, at least one photoemitter, at least one photodiode, at least one light emitting diode, and a semiconductor die.

16. The apparatus according to claim 14, wherein said at least one light detector includes one of a photoelectric receiver, a photodetector, a photodiode receiver, and a semiconductor die.

17. The device according to claim 11, wherein said pulse oximeter sensor elements include:

- means for transmitting light, and
- means for receiving light transmitted by said means for transmitting light.

5

18. A method for taking oximetry readings from a posterior pharyngeal region of a patient, said method comprising:

- coupling the device recited in claim 11 to a pulse oximeter,
- inserting the elongated member of the device recited in claim 11 through a
- 5 nasal cavity of the patient,
- aligning the pulse oximeter sensor elements of the device according to claim 11 with the posterior pharyngeal region of the patient, and
- contacting the pulse oximeter sensor elements of the device according to claim 11 with the posterior pharyngeal region of the patient.

19. A device according to claim 11, wherein said elongated member is made from flexible material including a portion capable of transmitting light.

20. A method for taking oximetry readings from a nasal mucosa of a patient, said method comprising:






coupling the device recited in claim 11 to a pulse oximeter,

5 inserting the elongated member of the device recited in claim 11 through a nasal cavity of the patient,

aligning the pulse oximeter sensor elements of the device according to claim 11 with the nasal mucosa of the patient, and

contacting the pulse oximeter sensor elements of the device according to claim 11 with the nasal mucosa of the patient.

1/1



INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 99/20234

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61B5/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 96 29927 A (SENSOR DEVICES, INC.) 3 October 1996 (1996-10-03) page 3, line 27 -page 4, line 29 page 7, line 16 -page 8, line 26	1-7, 11-17
Y	page 20, line 10 -page 24, line 19; figures 11,12	8,9,18, 19
Y	US 5 282 464 A (A. I. J. BRAIN) 1 February 1994 (1994-02-01) cited in the application	8,9,18, 19
A	column 1, line 37 - line 55 column 6, line 42 -column 7, line 23	10,20
A	WO 90 07907 A (NEURODYNAMICS, INC.) 26 July 1990 (1990-07-26) page 5, line 27 -page 8, line 2 figures 3,4	1-7, 11-17

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

14 December 1999

Date of mailing of the international search report

22/12/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Geffen, N

INTERNATIONAL SEARCH REPORT

Inter .nal Application No

PCT/US 99/20234

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category ²	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 357 954 A (G. SHIGEZAWA ET AL) 25 October 1994 (1994-10-25) column 4, line 42 -column 6, line 36 ---	1-20
A	US 5 329 922 A (J. L. ATLEE) 19 July 1994 (1994-07-19) column 2, line 63 -column 4, line 33 -----	1-20

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 99/20234

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9629927 A	03-10-1996	US 5743261 A US 5715816 A AU 711189 B AU 5529796 A EP 0817590 A JP 11502748 T	28-04-1998 10-02-1998 07-10-1999 16-10-1996 14-01-1998 09-03-1998
US 5282464 A	01-02-1994	CA 2100929 A,C DE 69302536 D DE 69302536 T EP 0580385 A	22-01-1994 13-06-1996 28-11-1996 26-01-1994
WO 9007907 A	26-07-1990	AU 4968790 A	13-08-1990
US 5357954 A	25-10-1994	NONE	
US 5329922 A	19-07-1994	NONE	